

BUILT O₂ LAST



The Oxlife Independence

Backed with a Standard
5-Year Warranty



Durability That Outlasts the Competition.

The Oxlife Independence by O2 Concepts is the only concentrator on the market with all light-weight metal construction and standard 5 year warranty. It was specifically designed to handle the rigors of 24/7 use. With continuous flow up to 3LPM and pulse settings up to 6 (96 mL), the Oxlife Independence is the ideal non-delivery solution for your most demanding oxygen patients.



- Patented ESA technology enables the Oxlife Independence to have the **longest battery life in its class**
- **Can be used on all settings** while plugged in a car (DC mode)
- **Integrated DC power supply** - no external brick
- **Durable exterior made of all light-weight metal** to survive your most demanding oxygen patients

- **FAA Approved**
- Convenient access to preventative maintenance door for **fast and easy pump filter change**
- Integrated cart with 6" wheels offers "best in class" mobility and **lighter overall weight**
- Custom split battery configuration allows for "hot swapping" of battery. **No loss of oxygen when switching battery**



Pulse Flow Settings



- Flow settings in .5 increments for better patient titration
- Large LCD screen with multi-color background (blue, red, yellow) – easy for visual and hearing impaired patients.

SETTING	DOSAGE (ML)
.5	8
1	16
1.5	24
2	32
2.5	40
3	48
3.5	56
4	64
4.5	72
5	80
5.5	88
6	96

Product Specifications*

Dimensions	Height: 20.2" • Width: 10.9" • Depth: 8"
Weight**	Device: 16.7 lbs • Battery: 1.35 lbs/each
Oxygen Flow Rate	Pulse Dose Settings 0.5-6 in 0.5 increments (8mL-96mL) 0.5-3 LPM in Continuous Mode in 0.5 LMP increments
Battery Duration***	5.75 hours @ 2 pulse at 20 bpm • 2.5 hours @ 2LPM continuous
Sound Level @ 2 Pulse	40 dBA
Battery Recharge Time****	1.5 hours - 1 battery • 2.5 hours - 2 batteries
Oxygen Concentration	87%-95.6% at Sea Level at all settings
Oxygen Output Pressure	5psig +/- 1 psig (34 +/- 7 kPa)
AC Power	Universal Input: 100-240 VAC • 50-60 Hz • 2 Amps Output 24 Volts • 6.3 Amps
DC Power	12 -15 VDC • 10 Amps
Operating Temperature	50°F (10°C) to 104°F (40°C)
Altitude Operating Range	0 - 13,123 Feet (0 - 4,000 Meters)
Transportation/Storage Temperature	-4°F (-20°C) to 140°F (60°C)
Transportation/Storage Humidity	0-95% Non-Condensing
Warranty	5 Year Limited • 1 Year on Accessories/Battery



*O2 Concepts reserves the right to change specifications of this product at anytime without notice

**Production weight does not include cart kit

***Battery duration shown is for extended battery system

****Battery recharge time will increase if unit is running while charging

Ordering Information

Part Description	Part Number
Systems	
Oxlife Independence POC Standard System The Oxlife Independence POC Standard System includes oxygen concentrator, 1 battery, pull handle and wheels, AC and DC power supplies, accessory bag and user manual.	800-0001-1
Oxlife Independence POC Extended Battery System The Oxlife Independence POC Extended Battery System includes oxygen concentrator, 2 batteries, pull handle and wheels, AC and DC power supplies, accessory bag and user manual.	800-0001-2
Accessories	
AC Power Cord/Power Supply	800-1022
DC Power Cord	800-1001
Battery - Lithium Ion Rechargeable	800-1002S
Accessory Carry Bag	800-1003
Battery Charger - Desk Top Single Bay	800-1004
Battery Charger - Multiple (6 Bay)	800-1005
Inlet Air Filter (Pack of 6)	800-1006
Wheels (2)	800-1007
User Manual	800-1008
Cart Kit (Includes Wheels and Pull Handle)	800-1010
Pull Handle Kit	800-1011
Pump Filter Kit	800-1013
Humidifier Kit	800-1015

**US Federal Law Restricts these devices to sale by or on the order of a physician*



914 N. Broadway, Suite 100
Oklahoma City, OK 73102

T: 877-867-4008
F: 877-867-1314
www.o2-Concepts.com



Proudly Made in the USA

